

LION

SERIES

650-2200 VA

LINE INTERACTIVE UPS



HOME/OFFICE




FEATURES

- LED Display (650-850)
- LCD Display (1200-1500-2200)
- Voltage Range, Operation Mode, Battery Charge and Load Quantity Monitoring via LCD Display (1200-1500-2200)
- Microprocessor-Based Digital Control
- Automatic Voltage Stabilization
- Automatic Breaker
- Frequency Adaptive
- User Friendly Alarm System
- Cold Start
- Auto Restart while AC is Recovering
- Simulated Sine Wave Output
- Intelligent Battery Management
- Short Circuit and Over Discharged Protection
- Automatically Charging Battery at UPS Off Mode
- USB Communication Port
- RJ11/RJ45 Protection

DETAILS

1. AC Input
2. Outlet
3. Breaker
4. RJ11/RJ45
5. USB
6. Fan



Optional outlets



400 VA ~ 800 VA
Plastic case



1200 VA ~ 1500 VA
Plastic case



600 VA ~ 800 VA
Metal case



POWER
FOR LIFE

Aytemiz
MAKELSAN

MODEL					
Capacity	650VA / 390W	850VA / 510W	1200VA / 720W	1500VA / 900W	2200VA / 1320W
INPUT					
Related Voltage	220/230 VAC				
Voltage Range	170-280 VAC (±%5)				
Frequency	50 Hz (±%10)				
OUTPUT					
Voltage Range	220 VAC				
Voltage Precision	±10% (Battery Mode)				
Frequency	50 Hz ±%1 (Akü Modu)				
Transfer Time	2-6ms Typical, 10ms max. Modified				
Waveform	Sine Wave (Battery Mode)				
EFFICIENCY					
Line Mode	Normal Mode: >95%, AVR Mode: >88%				
Battery Mode	>60%				
BATTERY					
Battery Configuration	1 x 12V/7Ah	1 x 12V/9Ah	2 x 12V/7Ah	2 x 12V/9Ah	2 x 12V/9Ah
Charge Current	1A				
Recharge/Charging Time	6-8 hours for Recharging up to 90% Capacity				
Backup Time	~16 min.	~20 min.	~30 min.	~50 min.	~50 min.
PROTECTION					
Full Protection	Overload, Short Circuit, Battery Charge-Discharge Protection				
INDICATION					
Display	LED		LCD		
ALARM					
Battery Mode	Sounding every 10 seconds				
Low Battery	Sounding every 1 seconds				
Overload	Sounding every 0.5 seconds				
Fault	Continuously Sounding				
ENVIRONMENTAL					
Operating Temperature	0 ~ 40°C				
Storage Temperature	-20°C ~ 55°C				
Relative Humidity	0 - 95°C (Non Condensing)				
Audible Noise (at 1m)	≤40 dB				
COMMUNICATION					
Communication Port	USB				
Software	Windows Family / Linux / Mac				
DIMENSIONS & WEIGHT	650VA	850VA	1200VA	1500VA	2200VA
Dimensions WxDxH (mm)	101 x 298 x 142		150 x 353 x 162		
Packaging Dimensions WxDxH (mm)	142 x 332 x 213		192 x 405 x 235		

Aytemiz-Makelsan reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Aytemiz-Makelsan products previously or subsequently sold. Aytemiz-Makelsan does not guarantee the items of the accuracy and completeness.