



Pro Max 24


USW-Pro-Max-24

Datasheet

In The Box


Marketing Images

[Installation Guide](#)



*Require UniFi Power Backup.
**Pair with UniFi Etherlighting Patch Cables for optimal brightness.

Zoom in



Zoom in

Mechanical

Dimensions

442 x 325 x 44 mm (17.4 x 12.8 x 1.7")

Weight

Without mounting brackets: 4.2 kg (9.3 lb)

With mounting brackets: 4.3 kg (9.5 lb)

Enclosure material

SGCC steel

Hardware

Management interface

Ethernet In-Band

Networking interface

(16) GbE RJ45 ports

(8) 1/2.5 GbE RJ45 ports

(2) 10G SFP+ ports

Total non-blocking throughput

56 Gbps

Switching capacity

112 Gbps

Forwarding rate

83.328 Mpps

Power method	(1) Universal input, 100—240V AC, 50/60 Hz (1) USP-RPS DC input
---------------------	--

Power supply	AC/DC, internal, 50W
---------------------	----------------------

Supported voltage range	100—240V AC
--------------------------------	-------------

Max. power consumption	50W
-------------------------------	-----

LCM display	(1) 1.3" touchscreen
--------------------	----------------------

Button	Factory reset
---------------	---------------

Ambient operating temperature	-5 to 40° C (23 to 104° F)
--------------------------------------	----------------------------

Ambient operating humidity	10 to 90% noncondensing
-----------------------------------	-------------------------

Certifications	CE, FCC, IC
-----------------------	-------------

Switching Features

Layer 2 features	IGMP snooping STP / RSTP with priorities and port-level disable Port isolation Storm control Voice VLAN Port mirroring LACP port aggregation Multicast / broadcast rate limiting MAC address blocking Flow control 802.1X control Jumbo frames Proprietary loop protection DHCP snooping / guarding Egress rate limit LLDP-MED Port restricted by MAC
-------------------------	---

	Device isolation with ACLs
Layer 3 features	DHCP for locally-managed networks DHCP relay Inter-VLAN routing between networks on same switch Static routing between local networks Network isolation with ACLs
Etherlighting™	
Ethernet	Locating Speed/link Native VLAN/network
SFP+	Locating Speed/link Native VLAN/network
LEDs	
System	Status
RPS	Status
Application Requirements	
UniFi Network	Version 8.0.24 and later